Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claims 1-21 (Canceled).

- 22. (Currently amended) A method for portion cutting a food item, comprising the steps of:
 - scanning at least one of a shape, a structure and/or a dimension of the food item at a first cutting stage by a measuring means;
 - determining, using a processor, a portion-cutting
 profile in connection with said scanning at the
 first cutting stage;
 - cutting the food item into strips at the first cutting stage in accordance with said portion-cutting profile;

 - cutting the strips into substantially quadratic

 rectangular pieces of predetermined weight and/or
 dimension at [[a]] said second cutting stage on
 the basis of additional scanning of at least one
 of a shape, a structure and/or a dimension of the
 strips at the second stage, said second cutting
 stage cutting said strips at a direction
 substantially perpendicular to the cutting
 performed at the first stage;

wherein said step of determining a portion-cutting profile at the first cutting stage comprises determining, in consideration of waste minimization, a predetermined dimensions and/or weights for the cutting-up of said food item into said strips and for the cutting-up of said strips into said substantially quadratic rectangular pieces, on the basis of said at least one of a shape, a structure and/or a dimension of said food item scanned at the first cutting stage and on the basis of said predetermined weight and/or dimensions, and

wherein said second cutting stage comprises two or more cutting devices having substantially parallel feeding directions.

- 23. (Original) A method for portion cutting a food item as set forth in claim 22, whereby said determining said portion-cutting profile comprises the step of planning the whole of a cutting sequence.
- 24. (Original) A method for portion cutting a food item as set forth in claim 22, whereby at least a part of said portion-cutting profile is carried out in said first cutting stage.

25. (Cancelled)

26. (currently amended) A method for portion cutting a food item as set forth in claim 22, wherein other scanning of the shape, structure and/or dimension of the strips is performed in at least one of in the two or more cutting

devices comprised in-of the second cutting stage.

- 27. (currently amended) A method for portion cutting a food item as set forth in claim 22, wherein a feeding direction of said two or more cutting devices of the second cutting stage is different from that of a first cutting device provided in said first cutting stage.
- 28. (currently amended) A method for portion cutting a food item as set forth in claim 22, wherein at least a part of said portion-cutting profile is communicated further to one or more of the two or more cutting devices of the second cutting stage.

29. (Cancelled)

- 30. (currently amended) A method for portion cutting a food item as set forth in claim 22, wherein a feeding direction for the two or more cutting devices of the second cutting stage lies substantially at right-angles to a feeding direction for a first cutting device provided in the first cutting stage.
- 31. (currently amended) A method for portion cutting a food item as set forth in claim 22, further comprising the step of manually placing the food item in a first cutting device provided in the first cutting stage and/or manually transferring the strips to at least one of one or more of the two or more cutting devices of comprised in the second cutting stage.
 - 32. (currently amended) A method for portion cutting a

food item as set forth in claim 22, further comprising the step of non-manually placing the food item in a first cutting device provided in the first cutting stage and/or non-manually transferring the strips to at lest one of one or more of the two or more cutting devices provided in ef the second cutting stage device.

Claim 33 (Canceled).

- 34. (Previously presented) An apparatus for portion cutting a food item as set forth in claim 41, wherein said processor is arranged to plan the whole of a cutting sequence, and thereby establish said portion-cutting profile.
- 35. (currently amended) An apparatus for portion cutting a food item as set forth in claim 41, wherein said first cutting <u>device</u> stage is adapted to carry out at least a part of said portion-cutting profile.
- 36. (currently amended) An apparatus for portion cutting a food item as set forth in claim 41, wherein further measuring means are arranged in each of said two or more additional cutting devices, each one second cutting stage for scanning at least one of a shape, a structure and/or a dimension of a subset of said strips.
- 37. (currently amended) An apparatus for portion cutting a food item as set forth in claim 41, wherein the processor is arranged to send at least a part of the portion cutting profile further to the <u>one or more</u> additional cutting devices <u>second cutting stage</u>.

- 38. (currently amended) An apparatus for portion cutting a food item as set forth in claim 41, which further comprises transfer means wherein said transporter is a conveyor for transferring one or more of the strips from the first cutting device stage to at least one of the one or more additional cutting devices second cutting stage.
- 39. (currently amended) An apparatus for portion cutting a food item as set forth in claim 41, which further comprises placing means for placing the food item in the first cutting device stage.
- 40. (currently amended) An apparatus for portion cutting a food item as set forth in claim [[41]] 48, wherein a feeding directions of the one two or more additional cutting devices provided in said second cutting stage is are different from that of [[a]] the first cutting device provided in said first cutting stage.
- 41. (Currently amended): An apparatus for portion cutting a food item <u>into pieces of substantially</u> rectangular shape, comprising:
 - a first cutting device including first measuring means for scanning at least one of a shape, a structure and/or a dimension of the food item—at a first cutting stage;
 - a processor for determining a portion-cutting profile
 in connection with said scanning;
 - a <u>first cutting unit included in said first cutting</u>
 device <u>first cutting stage</u> for cutting the food

- item into strips in accordance with said portioncutting profile;
- a transporter for transporting said strips to one or more additional cutting devices; and
- said one or more additional cutting devices, each

 comprising further measuring means for scanning
 at least one of a shape, a structure and/or a
 dimension of the strips and a cutting unit a
 second cutting stage for cutting the strips into
 substantially rectangular quadratic pieces of
 predetermined weight and/or dimension, said
 second cutting stage cutting said strips at a
 direction substantially perpendicular to the
 cutting performed at the first cutting stage;
- wherein said processor is adapted to determine said portion-cutting profile comprises determined in consideration of waste minimization and predetermined dimensions and/or weights for the cutting-up of said food item into said strips and for the cutting-up of said strips into said substantially quadratic rectangular pieces, on the basis of said at least one of a shape, a structure and/or a dimension of said food item;
- wherein said second cutting stage comprises two or
 more cutting devices having substantially
 parallel feeding directions.
- 42. (Cancelled).
- 43. (Currently amended) A method for portion cutting a food item, comprising the steps of:

- determining at least one physical attribute of the food item using a first measuring device;
- determining, using a processor, a portion-cutting profile utilizing said at least one physical attribute of the food and a desired physical attribute;
- first cutting the food item into strips at the first cutting stage by cutting in a first cutting direction, said cutting performed in accordance with said portion-cutting profile;
- transporting at least a portion of said strips to a
 second cutting stage;
- after said transporting, determining at least one

 physical attribute of the at least a portion of
 the strips using a second measuring device; and
- utilizing said at least one physical attribute of the
 at least a portion of the strips for second
 cutting said at least a portion of said strips
 into substantially quadratic rectangular pieces
 of the predetermined physical attribute at [[a]]
 said second cutting stage by cutting in a second
 cutting direction, said second cutting direction
 being substantially perpendicular to said first
 cutting direction;
- wherein said second outling stage comprises two or more cutting devices having substantially parallel feeding directions.
- 44. (Previously presented) The method of claim 43, wherein said second cutting is performed at the second

stage also in accordance with said portion-cutting profile and said portion cutting profile is determined in advance of both said first cutting and said second cutting.

- 45. (new) The method of claim 43, wherein said second cutting direction is substantially perpendicular to said first cutting direction.
- 46. (new) The method of claim 43, wherein said transporting includes changing a direction of travel of said strips.
- 47. (new) The apparatus of claim 41, wherein said transporter is adapted to change a direction of travel of said strips.
- 48. (new) the apparatus of claim 41, wherein said one or more additional cutting devices have substantially parallel feeding directions arranged such that each cutting stage cuts a different subset of said strips into pieces.
- 49. (new) The apparatus of claim 41, wherein said additional second cutting devices have substantially parallel feeding directions that are perpendicular to the feeding direction of the first cutting device.
- 50. (new) The method of claim 22, wherein said transporting includes changing a direction of travel of said strips.